

# INDEX

## RUBBER CHEMISTRY AND TECHNOLOGY

### VOLUME 52, 1979

#### AUTHOR INDEX\*

- ANDRIES, J. C., C. K. RHEE, R. W. SMITH, D. B. ROSS, AND H. E. DIEM, A surface study of ozone attack and antiozonant protection of carbon black loaded natural rubber compounds, (4) 823
- ANOLICK, C., G. S. COOK, AND C. W. STEWART, Flammability properties of carpets with polychloroprene latex foam underlayments, (4) 871
- ANZAI, S., see FUJIO, R., (1) 74
- AUDA, R. S., see OTTERSTEDT, C. W., (4) 899
- BERENS, A. S., Rotary shaft seals in the automotive industry (Abstract), (4) 901
- BERNARD, D., Natural rubber research—perspectives and strategies (Abstract), (2) 426
- BHOWMICK, A. K., R. MUKHOPADHYAY, AND S. K. DE, High temperature vulcanization of elastomers, (4) 725
- , AND S. K. DE, Dithiodimorpholine-based accelerator system in tire tread compound for high temperature vulcanization, (5) 985
- BLODGETT, R. B., Ethylene-propylene rubber and crosslinked polyethylene as insulations for 90°C medium voltage cables, (2) 410
- BODY, R. W., see COMEN, A. L., (2) 431
- BOYER, A. H., see MERCER, H. N., (2) 377
- BRAME, E. G. JR., AND H. E. HOLMQUIST, <sup>13</sup>C NMR analysis of carbon-13 enriched ethylene copolymers with propylene, (1) 1
- BRAZIER, D. W., AND G. H. NICKEL, Application of TMA for rapid evaluation of low-temperature properties of elastomer vulcanizates, (4) 735
- BREIDENBACH, R. F., AND G. J. LAKE, Mechanics of fracture in two-ply laminates, (1) 96
- BRICHZIN, D., see KLINGENSMITH, W. H., (2) 434
- BRIGGS, G. J., J. M. HOLMES, AND Y. K. WEI, Effect of labile crosslinked SBR on the green strength and hysteresis of radial tire compounds (Abstract), (4) 897
- BROWN, W. A., D. E. SCHLEIFER, AND A. C. PATEL, Void volume and the identification of recovered carbon blacks (Abstract), (4) 896
- BRULLO, R. A., W. DE MOULLY, AND A. T. WORM, A new class of processing agents for elastomers (Abstract), (4) 902
- BRUZZONE, M., Elastomer structures and cold crystallization, (1) 207
- BULLMAN, G. W., see STIEHLER, A. D., (2) 255
- BURGESS, K. A., AND C. E. SCOTT, Outlook for carbon black development (Abstract), (2) 427
- CADLE, S. H., AND R. L. WILLIAMS, Gas and particle emissions from automobile tires in laboratory and field studies, (1) 146
- CASPARY, R., AND P. KRETSCHMER, Ultrasonic measurements with rubber compounds during extrusion, (2) 294
- CHEHEBAR, A. L., AND E. J. GALLI, Optimum choice for reference temperature in evaluation of curing cycles, (2) 286
- CHERICO, V. E., see VEITH, A. G., (4) 748
- CODDINGTON, D. M., Inflation pressure loss in tubeless tires—effects of tire size, service, and construction, (5) 905
- COLLINS, E. A., D. J. HOFFMAN, AND P. L. SONI, Rheology of plastisols of poly(vinyl chloride), (3) 676
- COMEN, A. L., AND R. W. BODY, Peroxide cured EPDM in wire and cable applications (Abstract), (2) 431
- COOK, G. S., see ANOLICK, C., (4) 871
- COTTEN, G. R., Influence of carbon black on processability of rubber stocks. II. extrusion, (1) 187

\* Prepared by L. E. Gwin.

- , Influence of carbon black on processability of rubber stocks. IV. kinetics of extrusion shrinkage, (1) 199
- CURTISS, W. W., see KNILL, R. B., (2) 428
- DE, S. K., see MUKHOPADHYAY, R., (2) 263
- , see BHOWMICK, A. K., (4) 725
- , see BHOWMICK, A. K., (5) 985
- DECKER, G. E., see STIEHLER, A. D., (2) 255
- DE MARCO, R. D., New generation polyacrylate elastomers, (1) 173
- DE MOULLY, W., see BRULLO, R. A., (4) 902
- DEVINEY, M. L., see MERCER, H. N., (2) 377
- DIEM, H. E., see ANDRIES, J. C., (4) 823
- DIMAURO, P. J., H. L. PARIS, AND M. A. FATH, Wax protection, (5) 973
- DUNN, J. R., H. A. PFISTERER, AND J. J. RIDLAND, NBR vulcanizates resistant to high temperature and "sour gasoline", (2) 331
- EDWARDS, D. C., AND K. SATO, Nitrile rubber functionalized for silica reinforcement, (1) 84
- EDWARDS, K., see LAUTENSCHLAGER, F., (5) 1050
- EDWARDS, W. S., see TIMAR, J., (2) 319
- ERMAN, B., AND P. J. FLORY, Rubber elasticity in the range of small uniaxial tensions and compressions. Results for poly(dimethylsiloxane), (1) 127
- FALENDER, J. R., AND G. S. Y. YEH, The effect of crosslink distribution on elastomeric properties. II. Poly(dimethylsiloxane) networks prepared from polymers having high, intermediate, and low site selectivity (Abstract), (2) 425
- FARRIS, R. J., Rubber heat engines, analysis and theory, (1) 159
- FATH, M. A., see DIMAURO, P. J., (5) 973
- FLORY, P. J., Theory of elasticity of polymer networks. The effect of local constraints on junctions, (1) 110
- , see ERMAN, B., (1) 127
- FREAKLEY, P. K., AND W. Y. WAN INDRIS, Visualization of flow during the processing of rubber in an internal mixer, (1) 134
- FROHLICH, A., see KLINGENSMITH, W. H., (2) 434
- FUJIO, R., M. KITAYAMA, N. KATAOKA, AND S. ANZAI, Effects of sulfur on the peroxide cure of EPDM and divinylbenzene compounds, (1) 74
- GABRIEL, A. P., EPR telephone drop wire, a new dimension in telephone drop wire, (2) 400
- GALLI, E. J., see CHEHEBAR, A. L., (2) 286
- GENT, A. N., AND G. R. HAMED, Peel mechanics for an elastic-plastic adherend, (5) 1057
- GHATGE, N. D., AND N. N. MOLDAH, The vulcanization of styrene-butadiene rubber with 2-pentadecylbenzoquinone dioxime, (2) 353
- GOETTLER, L. A., R. I. LEIB, AND A. J. LAMBRIGHT, Short fiber reinforced hose—a new concept in production and performance, (4) 838
- GOKEN, G. L., The role of elastomers in adhesives (Abstract), (4) 901
- GRAESSLEY, W. W., see PEARSON, D. L., (2) 304
- GREGORY, M. J., Selection of carbon black fillers for rubber springs, (5) 996
- HAGER, T., A. MACARTHUR, D. MCINTYRE, AND R. SEEGER, Chemistry and structure of natural rubbers, (4) 693
- HAMED, G. R., see GENT, A. N., (5) 1057
- HARRELL, E. R., see NAKAJIMA, N., (1) 9
- , see NAKAJIMA, N., (5) 962
- HEWITT, N. L., see WAGNER, M. P., (4) 805
- HO, C. C., AND J. R. JOHNSON, An improved thermoplastic elastomer for gasket applications (Abstract), (4) 902
- HOFFMAN, D. J., see COLLINS, E. A., (3) 676
- HOLMES, J. M., see BRIGGS, G. J., (4) 897
- HOLMQUIST, H. E., see BRAME, E. G. JR., (1) 1
- HORVATH, J. W., High performance nitrile rubber automotive fuel hose, (4) 883
- IZAWA, M., see MINOURA, Y., (5) 920
- JOHNSON, J. R., see HO, C. C., (4) 902
- JOWETT, F., The protection of rubber by petroleum waxes (Abstract), (4) 895

- KAINRADL, P., Critical reflections on physical and technological test methods in the rubber industry, (2) 232
- KATAOKA, N., see FUJIO, R., (1) 74
- KILLGOAR, P. C., see TABAR, R. J., (4) 781
- KITAYAMA, M., see FUJIO, R., (1) 74
- KLINGENSMITH, W. J., D. BRICZIN, AND A. FROHLICH, Processing agents in elastomer compounds for the cable industry (Abstract), (2) 434
- KNILL, R. B., W. W. CURTISS, AND J. P. URBON, Current trends in tire technology (Abstract), (2) 428
- KOBAYASHI, K., see KUSANO, T., (4) 773
- KOHMOTO, S., see MINOURA, Y., (5) 920
- KRATOCHVIL, P., see STEJSKAL, J., (1) 20
- KRAUS, G., AND K. W. ROLLMAN, The entanglement plateau in the dynamic modulus of rubbery styrene-diene block copolymers. Significance to pressure sensitive adhesive formulations, (2) 278
- KRAUSE, J. W., Automatic control and measurement of the tread extrusion process (Abstract), (4) 903
- KRETSCHMER, P., see CASPARY, R., (2) 294
- KRUEGER, R. A., Future directions in elastomer research and development (Abstract), (2) 426
- KUSANO, T., K. KOBAYASHI, AND K. MURAKAMI, Mechanical chain scission in rubber vulcanizate at low temperatures, (4) 773
- LAKE, G. J., see BREIDENBACH, R. F., (1) 96
- LAMBRIGHT, A. J., AND J. B. PUTMAN, Salt bath curing for the wire and cable industry (Abstract), (2) 432
- , see GOETTLER, L. A., (4) 838
- LARSEN, E. R., AND R. B. LUDWIG, Chemical theory and mechanism of halogen's flame suppressing properties (Abstract), (2) 430
- LAUTENSCHLAGER, F. K., Model compound vulcanization. Part I., (2) 213
- , AND P. ZEEMAN, Model compound vulcanization. Part II., (5) 1030
- , Model compound vulcanization. Part III. The relationships between sulfidic product yield and stress-strain properties, (5) 1044
- , AND K. EDWARDS, Model compound vulcanization. Part IV. Comparative assessment of a sulfenamide accelerator and a triazine-type accelerator, (5) 1050
- LE BRAS, J., AND E. PAPIRER, The filler-elastomer chemical link and the reinforcement of rubber, (1) 43
- LEE, B., On the reinforcement of uncured and cured rubber polymer composite materials and its relationship to dispersive mixing—an interpretation of cure meter rheographs of carbon black loaded SBR and *cis*-polybutadiene compounds, (5) 1019
- LEIB, R. I., see GOETTLER, L. A., (4) 838
- LOU, A. Y. C., AND J. D. WALTER, Interlaminar shear strain measurements in cord rubber composites, (4) 792
- LUDWIG, R. B., see LARSEN, E. R., (2) 430
- LUTHER, R., Performance requirements for rubber-insulated cables in nuclear generating stations (Abstract), (2) 432
- MAC ARTHUR, A., see HAGER, T., (4) 693
- MARSH, H. A., see SCHOENBERG, E., (3) 526
- MARSLAND, J. E., Marketing cost-performance analysis for olefinic thermoplastic elastomers (Abstract), (2) 435
- MATSUO, T., see MINOURA, Y., (5) 920
- MC CORMICK, C. E., see WEST, J. R., (4) 896
- MC INTYRE, D., see HAGER, T., (4) 693
- MEIER, J. F., G. E. RUDD, AND D. F. WEIR, Creep resistant elastomer formulations, (1) 50
- MERCER, H. N., A. H. BOYER, AND M. L. DEVINEY, 3-D carbon black primary structure characterization via a new electron microscopy-photogrammetry technique, (2) 377
- MEYER, D. A., Research direction in non-tire rubber products (Abstract), (2) 428
- MINOURA, Y., S. YAMASHITA, H. OKAMOTO, T. MATSUO, M. IZAWA, AND S. KOHMOTO, Crosslinking and mechanical properties of liquid rubber. I. Curative effect of aliphatic diols, (5) 920
- MOLDAR, N. N., see GHATGE, N. D., (2) 353
- MORGAN, R. M., Nonlead stabilization of chlorinated polyethylene in wire and cable (Abstract), (2) 434

- MORIN, P. R., Olefinic thermoplastic elastomer applications as jacketing and insulating materials for wire and cable (Abstract), (2) 433
- MUKHOPADHYAY, R., AND S. K. DE, Effect of vulcanization temperature and different fillers on the properties of efficiently vulcanized natural rubber, (2) 263
- , see BHOWMICK, A. K., (4) 725
- MURAKAMI, K., see KURANO, T., (4) 773
- NAKAJIMA, N., AND E. R. HARRELL, Method of obtaining viscosity curves with Mooney rheometer, (1) 9
- , AND —, Correction for edge effect of Mooney rheometer, (5) 962
- NELSON, P. D., AND R. F. OHM, Fluid resistance of Norsorex polynorbornene (Abstract), (2) 435
- , AND —, Heat resistance of Norsorex polynorbornene (Abstract), (4) 903
- NICKEL, G. H., see BRAZIER, D. W., (4) 735
- NYE, H. F., Specification and polymers used in the cable industry (Abstract), (2) 431
- OHM, R. F., see NELSON, P. D., (2) 435
- , see NELSON, P. D., (4) 903
- OKAMOTO, H., see MINOURA, Y., (5) 920
- OTTERSTEDT, C. W., AND R. S. AUDA, Factors influencing the temperature rise of EPDM in continuous vulcanization media (Abstract), (4) 899
- PAPIRER, E., see LE BRAS, J., (1) 43
- PARIS, H. L., see DIMAURO, P. J., (5) 973
- PATEL, A. C., AND E. J. WEAVER, An experiment to characterize carbon black via capillary rheometer (Abstract), (2) 429
- , see BROWN, W. A., (4) 896
- PATEL, H. P., see WALTER, J. D., (4) 710
- PEARSON, D. L., AND W. W. GRAESSLEY, The structure of rubber networks with multifunctional junctions, (2) 304
- PERCIVAL, W. C., see SIMPSON, M. B. H., (4) 899
- PETT, R. A., see TABAR, R. J., (4) 781
- PFISTERER, H. A., see DUNN, J. R., (2) 331
- PHILLIPS, B. A., AND R. P. TAYLOR, Polyurea dispersions for RIM applications, (4) 864
- PIERCE, O. R., see WARRICK, E. L., (3) 437
- POLMANTEER, K. E., see WARRICK, E. L., (3) 437
- PORTER, L. S., AND H. L. STEPHENS, Effect of compounding variations on the properties of guayule rubber, (2) 361
- PUTMAN, J. B., see LAMBRIGHT, A. J., (2) 432
- RAILSBACK, H. E., see WILDER, C. R., (4) 895
- RAINS, R. K., see SHEN, H. S., (4) 764
- RHEE, C. K., see ANDRIES, J. C. (4) 823
- RIDLAND, J. J., see DUNN, J. R., (2) 331
- ROBERTS, A. D., Looking at rubber adhesion, (1) 23
- ROLLMAN, K. W., see KRAUS, G., (2) 278
- ROSS, D. B., see ANDRIES, J. C., (4) 823
- RUDD, G. E., see MEIER, J. F., (1) 50
- SAAM, J. C., see WARRICK, E. L., (3) 437
- SALOVEY, R., Technology transfer between rubber and plastics industries (Abstract), (2) 429
- SALTMAN, W. M., see SCHOENBERG, E., (3) 526
- SATO, K., see EDWARDS, D. C., (1) 84
- SCHLEIFER, D. E., see BROWN, W. A., (4) 896
- SCHOENBERG, E., H. A. MARSH, S. J. WALTERS, AND W. M. SALTMAN, Polyisoprene, (3) 526
- SCOTT, C. E., see BURGESS, K. A., (2) 427
- SCOTT, G., AND K. V. SMITH, Mechanisms of antioxidant action: Rubber bound antioxidants based on nitrones—I. Non-sulfur vulcanizates, (5) 949
- SEEGER, R., see HAGER, T., (4) 693
- SEYMOUR, D. C., The theory of power cable vulcanization without steam (Abstract), (2) 433
- SHEN, H. S., AND R. K. RAINS, Scale-up of short fiber composite mixing, (4) 764
- SIMPSON, M. B. H., AND W. C. PERCIVAL, The exothermic decomposition of litharge-elastomer dispersions (Abstract), (4) 899

- SMITH, K. V., see SCOTT, G., (5) 949  
SMITH, R. W., see ANDRIES, J. C., (4) 823  
SMITH, W. C., A historical review of elastomers in wire and cable (Abstract), (2) 429  
SOLOMON, T. S., Adhesion retention of tire cords using Carbo-set resins in cord adhesives (Abstract), (4) 898  
SONI, P. L., see COLLINS, E. A., (3) 676  
SOUTHERN, E., AND A. G. THOMAS, Studies of rubber abrasion, (5) 1008  
STEJSKAL, J., AND P. KRATOCHVIL, The conversion chemical heterogeneity of random butadiene-styrene copolymers, (1) 20  
STEPHENS, H. L., see PORTER, L. S., (2) 361  
STEWART, C. W., see ANOLICK, C., (4) 871  
STIEHLER, A. D., G. E. DECKER, AND G. W. BULLMAN, Determination of hardness and modulus of rubber with spherical indentors, (2) 255  
TABAR, R. J., P. C. KILLGOAR, AND R. A. PETT, A fatigue resistant polychloroprene compound for high temperature dynamic applications, (4) 781  
TAYLOR, R. P., see PHILLIPS, B. A., (4) 864  
THOMAS, A. G., see SOUTHERN, E., (5) 1008  
TIMAR, J., AND W. S. EDWARDS, Compounding bromobutyl for heat resistance, (2) 319  
TOKITA, N., Analysis of band formation in mill operation, (2) 387  
URBON, J. P., see KNILL, R. B., (2) 428  
VAIDYA, U. I., Flame retarded EPDM integral insulation jacket compositions with excellent heat resistance and electrical stability (Abstract), (2) 430  
VANDERMAR, B. C., Reciprocating and static seals for automatic transmissions (Abstract), (4) 900  
VAN OOI, W. J., Fundamental aspects of rubber adhesion to brass plated steel tire cords, (3) 605  
VEITH, A. G., AND V. E. CHIRICO, A quantitative study of the carbon black reinforcement system of tire tread compounds, (4) 748  
VIAL, T. M., A new specialty elastomer from thiodiethanol (Abstract), (4) 900  
WAGNER, M. P., AND N. L. HEWITT, New developments in a dynamic wire adhesion test, (4) 805  
WALTER, J. D., AND H. P. PATEL, Approximate expressions for the elastic constants of cord-rubber laminates, (4) 710  
—, see LOU, A. Y. C., (4) 792  
WALTERS, S. J., see SCHOENBERG, E., (3) 526  
WAN IDRIS, W. Y., see FREAKLEY, P. K., (1) 134  
WARRICK, E. L., O. R. PIERCE, K. E. POLMANTEER, AND J. C. SAAM, Silicone elastomer developments, (3) 437  
WEAVER, E. J., see PATEL, A. C., (2) 429  
WEI, Y. K., see BRIGGS, G. J., (4) 897  
WEIR, D. F., see MEIER, J. F., (1) 50  
WEST, J. R., AND C. E. MC CORMICK, Assessing the relationship of carbon black properties to rolling resistance of a tread compound containing carbon black (Abstract), (4) 896  
WILDER, C. R., AND H. E. RAILSBACK, Repeatability of modulus specification testing of carbon black (Abstract), (4) 895  
WILLIAMS, R. L., see CADLE, S. H., (1) 146  
WORM, A. T., see BRULLO, R. A., (4) 902  
YAMASHITA, S., see MINOURA, Y., (5) 920  
YEH, G. S. Y., see FALENDER, J. R., (2) 425  
ZEEMAN, P., see LAUTENSCHLAGER, F. K., (5) 1030

## SUBJECT INDEX\*

- Abrasion, theory of, (5) 1008
- Abrasion resistance, carbon black-containing elastomers, (2) 427
  - tire tread compounds, (4) 748
- Abstracts of papers: Fall 1978 Meeting, (2) 425; Spring 1979 Meeting, (4) 895
- Accelerators, dithiodimorpholine, for high temperature vulcanization, (5) 985
  - efficiency, in model compound vulcanization, (5) 1030
  - level effect on model compound vulcanization, (2) 213
  - model compound vulcanization using, (5) 1030
- Acrylic elastomers, properties of, (1) 173
- Acrylic resin, tire cord adhesive application, (4) 898
- Acrylonitrile-butadiene copolymers, see Nitrile Rubber
- Acrylonitrile content, effect on NBR fuel permeability, (2) 331
- Activation energy, effect on reference temperature optimization for curing cycles, (2) 286
- Adhesion, rubber, mechanism of, (1) 23
  - rubber-brass (review), (3) 605
  - rubber-cord, measurement of, (2) 232
  - rubber-wire, dynamic test for, (4) 805
- Adhesives, elastomers role in, (4) 901
  - peel mechanics of, (5) 1057
  - pressure-sensitive, dynamic modulus of, (2) 278
  - silicone rubber applications in (review), (3) 437
  - tire cord, acrylic resin in, (4) 898
- Adiabatic analysis, of rubber heat engine, (1) 159
- Aerospace applications, silicone elastomers (review), (3) 437
- Aging, measurement of, (2) 232
- Air permeability, of polynorbornene, (2) 435
- Air pollution, tire contribution to, (1) 146
- Akasaka-Hirans equation, elastic constants of rubber-cord composites, (4) 710
- Alfin catalyst, isoprene polymerization (review), (3) 526
- Alkali, isoprene polymerization catalysts (review), (3) 526
- Antimony oxide, use in flame retardant EPDM jacket insulation, (2) 430
- Antioxidant, bound, from N-phenyl nitrones, (5) 949
  - bound, in NBR fuel hose, (4) 883
  - effect on bromobutyl heat resistance, (2) 319
- Antiozonant, mechanism of elastomer protection, (4) 823
- Attenuated total reflectance spectroscopy (ATR), use in NR antiozonant study, (4) 823
- Authors, Guide for, (3) G63
- Automobile fascia, reaction injection molding of, (4) 864
- Automotive applications, of silicone rubber (review), (3) 437
- Automotive hose, NBR in, (4) 883
- Backrolling, prevention of during rubber milling, (2) 387
- Balata, chemistry and structure of, (4) 693
- Banbury, see internal mixer
- Band formation, analysis of during milling, (2) 387
- Band formation index, use in rubber milling, (2) 387
- Benzoyl peroxide, crosslinking agent for poly(dimethylsiloxane), (2) 425
- Best Paper Awards, Fall 1978 Meeting, (2) G36; Spring 1979 Meeting, (5) G104
- Biomedical applications, of silicone rubber (review), (3) 437
- Bis(2-ethylamino-4-diethylamino-6-triazinyl) disulfide, NR accelerator, (5) 1050
- $\alpha, \alpha'$ -Bis(t-butylperoxy)diisopropylbenzene, curative for EPDM cable insulation, (2) 431
- Blends (see also specific materials), high temperature vulcanization of, (4) 725
- Block copolymers, entanglement plateau in the dynamic modulus of, (2) 278
- Bloom, rubber adhesion effect, (1) 23
- Bonding agents, effect on rubber-brass adhesion (review), (3) 605
- Book reviews, "Developments in Polymer Characterization—1", (3) G71
  - "Developments in Polyurethane", (5) G108,
  - "Elastomer Criteria for Engineering Design", (5) G109
  - "Handbook of Thermoplastic Elastomers", (4) G98
  - "Kautschuk Lexicon", (1) G25
  - "Physical Testing of Rubbers", (4) G98
  - "Rubber Chemistry", (3) G71
  - "Science and Technology of Polymer Processing", (5) G108
  - "Science and Technology of Rubber", (1) G25
  - "The Vanderbilt Rubber Handbook", (1) G25
  - "Theory and Practice of Engineering with Rubber", (2) G50
- Boric acid, esters of, chlorinated polyethylene stabilizers, (2) 434
- Brass, adhesion to rubber (review), (3) 605
- Brass adhesion, dynamic test for, (4) 805

\* Prepared by L. E. Gwin.

- Bromine, flame suppressing mechanism of, (2) 430
- Bromobutyl rubber (BIIR), heat resistance of, (2) 319
- Burst strength, of oriented fiber-reinforced hose, (4) 838
- Bushing, NR, guayule, and IR comparison in, (2) 361
- Butadiene, copolymer with styrene, entanglement plateau in dynamic modulus of, (2) 278
- Butadiene-acrylonitrile rubber, see Nitrile Rubber
- Butadiene-styrene rubber, see styrene-butadiene rubber
- Butyl rubber (IIR), electrical cable specifications for, (2) 431
- Cable, electrical, specifications for, (2) 431
- Cable insulation, continuous vulcanization of, (2) 433
- nonlead stabilizers for, (2) 434
- peroxide curatives for EPDM, (2) 431
- requirements in nuclear power plants, (2) 432
- review of elastomers in, (2) 429
- thermoplastic elastomers in, (2) 433
- Cable, power, use of EPR insulation, (2) 410
- Cadmium oxide, activation of fuel-resistant NBR, (2) 331
- Calcium salt, of fatty acid, processing aid for cable insulation, (2) 434
- Capillary rheometer, carbon black characterization with, (2) 429
- use for void volume measurements, (4) 896
- Carbon-13, use in NMR analysis of EPR, (1) 1
- Carbon black, aggregation during mixing, (5) 1019
- characterization using capillary rheometer, (2) 429
- development outlook for, (2) 427
- effect on EV-cured NR properties, (2) 263
- effect on rubber processability, (1) 199
- effect on SBR extrusion, (2) 294
- graft polymer with IR, (1) 43
- identification after recovery, (4) 896
- modulus specification testing of, (4) 895
- NR springs containing, (5) 996
- processability effect of, (1) 187
- property relation to rolling resistance, (4) 896
- three dimensional characterization of, (2) 377
- tire tread reinforcement, (4) 748
- Carboset, see acrylic resin
- Carpet, flammability of, (4) 871
- Cashew nut shell liquid, synthesis of 2-pentadecylbenzoquinone dioxime from, (2) 353
- Castilla, chemistry and structure of NR from, (4) 693
- Cellulose fiber, mixing with rubber, (4) 764
- orientation in hose, (4) 838
- Chain scission, of NR at low temperatures, (4) 773
- Chicle, chemistry and structure of NR from, (4) 693
- Chlorine, flame suppressing mechanism of, (2) 430
- Chloroprene rubber, see polychloroprene
- Chromatography, gas, silicone rubber analysis (review), (3) 437
- Chromatography, gas-liquid, accelerator efficiency evaluation using, (5) 1030
- use in model compound vulcanization, (2) 213
- Coatings, silicone rubber applications (review), (3) 437
- Cobalt, bonding agents containing (review), (3) 605
- effect on dynamic wire adhesion, (4) 805
- Compression, uniaxial, effect on poly(dimethylsiloxanes), (1) 127
- Compression creep, of elastomers, (1) 50
- Compression set, of CR at high temperatures, (4) 781
- of IR vulcanizates (review), (3) 526
- Compression stress relaxation, of thermoplastic elastomer gaskets, (4) 902
- Computer, continuous infrared vulcanization optimization, (2) 433
- use for cure cycle reference temperature optimization, (2) 286
- Contact adhesives, elastomers in, (4) 901
- Continuous vulcanization, of EPDM, (4) 899
- salt bath, of wire and cable insulation, (2) 432
- Conversion, effect on chemical composition of random SBR, (1) 20
- Coordination catalysts, for *cis*-polyisoprene (review), (3) 526
- Copper, catalysis of NBR aging in sour gasoline, (2) 331
- effect on dynamic brass-coated steel adhesion, (4) 805
- Cord, steel, fracture mechanism of rubber laminates, (1) 96
- Cord, tire, composites with rubber, (4) 792
- Cost-performance analysis, of thermoplastic elastomers, (2) 435
- Crack growth, in tires, measurement of, (2) 232
- of rubber-cord laminates, (1) 96
- Creep resistance, of elastomer formulations, (1) 50
- Crosslink density, of EV-cured NR, (2) 263
- effect on NR low temperature properties, (4) 773
- effect on rubber adhesion, (1) 23
- high temperature vulcanization effect on, (4) 725
- of poly(dimethylsiloxanes) of varying site selectivity, (2) 425
- of rubber networks, (2) 304
- Crosslink distribution, elastomeric property effect on poly(dimethylsiloxane), (2) 425

- Crystallinity, in IR (review), (3) 526
- Crystallization, cold, glass transition effect on, (1) 207
- Cure kinetics, of peroxide-cured EPDM-divinylbenzene compounds, (1) 74
- Cure mechanism, of acrylic elastomers, (1) 173
- Cure properties, of guayule rubber, NR, and IR, (2) 361
- N-cyclohexylbenzothiazole-2-sulfenamide, model compound vulcanization, (5) 1030
- Cyclopolyisoprene formation during isoprene polymerization (review), (3) 526
- Delamination, of rubber-cord composites, (4) 792
- Dental applications, silicone rubber (review), (3) 437
- Dicumyl peroxide, curative for EPDM cable insulation, (2) 431
- sulfur effect on EPDM cure, (1) 74
- Die, extrusion, effects on oriented fiber hose reinforcements, (4) 838
- Dielectric strength, of EPDM telephone drop wire, (2) 400
- Differential scanning calorimetry (DSC), of litharge-elastomer dispersion decomposition, (4) 899
- Diisocyanate, effect on liquid polyurethane properties, (5) 920
- Dimensional analysis, use in mill band formation analysis, (2) 387
- 2,5-Dimethyl-2,5-di(*t*-butylperoxy)hexane, crosslinking agent for poly(dimethylsiloxane), (2) 425
- N,N'-dioctyl-*p*-phenylenediamine, antioxidant mechanism in NR, (4) 823
- Diol, effect on liquid polyurethane properties, (5) 920
- Disk fatigue test, for dynamic wire adhesion, (4) 805
- Dispersion, of carbon black, from rheographs, (5)
- of cellulose fibers in rubber, (4) 764
- 1,1-Di-*t*-butylperoxy-3,3,5-trimethylcyclohexane, sulfur effect on EPDM cure, (1) 74
- Dithiocarbamate, curatives for heat resistant bromobutyl rubber, (2) 319
- Dithiodimorpholine, accelerator for high temperature vulcanization, (5) 985
- Divinylbenzene, sulfur effect on EPDM cure with, (1) 74
- Drop wire, EPDM usage in, (2) 400
- Dynamic mechanical properties, of peroxide-cured EPDM-divinylbenzene compounds, (1) 74
- Dynamic properties, carbon black effect on, (5) 996
- of CR at high temperatures, (4) 781
- of guayule rubber, NR, and IR, (2) 361
- Edge effect, Mooney rheometer correction for, (5) 962
- Efficient vulcanization (EV), temperature and filler effects on NR, (2) 263
- Elastic constants, of cord-rubber laminates, (4) 710
- Elasticity index, pressure-temperature effects during SBR extrusion, (2) 294
- Elasticity, of poly(dimethylsiloxane) during uniaxial compression and tension, (1) 127
- theory of, local constraint effect on junctions, (1) 110
- Elastomers, future research directions, (2) 426
- Electrical properties, of silicone elastomers (review), (3) 437
- Electrodes, silicone rubber use as (review), (3) 437
- Electron microscopy, carbon black structure characterization, (2) 387
- of peroxide-cured EPDM-divinylbenzene, (1) 74
- Electronics, silicone rubber applications (review), (3) 437
- Electrostatic force, rubber adhesion effect, (1) 23
- Emissions, gas and particulate, from tires, (1) 146
- Engine, heat, analysis and theory of, (1) 159
- Entanglement, rubber network property effect of, (2) 304
- Environment, silicone rubber impact on (review), (3) 437
- Epichlorohydrin rubber, creep resistance of, (1) 50
- processing agent for, (4) 902
- Epoxidation, of IR (review), (3) 526
- Epoxy groups, in silica-reinforced functionalized NBR, (1) 84
- Epoxy resin, stabilizer for chlorinated polyethylene, (2) 434
- Ethylene, latex flow stimulant, (2) 426
- Ethylene copolymer, with methyl acrylate, carboxylated, (2) 426
- with vinyl acetate, electrical insulation specifications for, (2) 431
- Ethylene-propylene rubber (EPR), cable insulation requirements in nuclear power plants, (2) 432
- creep resistance of, (1) 50
- electrical cable specifications for, (2) 431
- NMR analysis of, (1) 1
- use for cable insulation, (2) 410
- Ethylene-propylene-diene copolymer (EPDM), blend with polypropylene, (2) 429
- carbon black characterization in, (2) 429
- computer optimization of continuous vulcanization of, (2) 433
- continuous vulcanization of, (4) 899
- creep resistance of, (1) 50
- extrusion shrinkage of, (1) 187
- flame retardant insulation jackets of, (2) 430
- peroxide curatives for, (2) 431
- processing agent for, (4) 902



- sulfur effect on peroxide cure of, (1) 74  
 telephone drop wire, use as, (2) 400  
 Extrusion, carbon black effect on shrinkage, (1) 187  
 continuous vulcanization of EPDM, (4) 899  
 kinetics of shrinkage during, (1) 199  
 oriented fiber in hose, (4) 838  
 tread rubber, automatic control of, (4) 903  
 ultrasonic measurements during, (2) 294
- Failure mechanism, of rubber-cord laminates, (1) 96  
 Fatigue resistance, of CR vulcanizates, (4) 781  
 Fatty acids, processing aids for cable insulation, (2) 434  
 Fibers, cellulose, mixing of rubber composites, (4) 764  
 orientation in hose, (4) 838  
 silicone rubber reinforcement by (review), (3) 437  
*Ficus elastica*, chemistry and structure of NR from, (4) 693  
 Fill factor, effect on mixing uniformly, (1) 134  
 Filler-polymer interaction, during high temperature vulcanization, (4) 725  
 Film, polyester, peel mechanics of, (5) 1057  
 Flammability, of carpet with CR foam underlayment, (4) 871  
 Flame resistance, of electrical insulation, (2) 431  
 of EPDM cable insulation, (2) 430  
 Flame suppression, mechanics of, (2) 430  
 Flex fatigue, of NR, (5) 996  
 Flexural modulus, of polyurethanes, (4) 864  
 Flow, elastomeric, in internal mixers, (1) 134  
 Fluid resistance, of acrylic elastomer, (1) 173  
 of polynorbornene, (2) 435  
 of poly(thiodiethanol), (4) 900  
 Fluorine, flame suppressing mechanism of, (2) 430  
 Fluoroelastomers, automatic transmission seals, (4) 900  
 decomposition of litharge dispersions in, (4) 899  
 oil seals, (4) 901  
 phosphonitrilic, developments in, (2) 426  
 Foam, CR latex for carpet, (4) 871  
 polyurethane, in automotive fascia, (2) 428  
 silicone rubber applications (review), (3) 437  
 Fractionation, of NR, (4) 693  
 Fracture mechanics, of rubber-cord laminates, (1) 96  
 rubber abrasion applications of, (5) 1008  
 Free energy, elastic, polymer network effect, (1) 110  
 Friction, rubber adhesion effect, (1) 23  
 Fuel hose, bound antioxidants for NBR, (4) 883  
 Fuel resistance, of NBR, (2) 331  
 Gamma irradiation, crosslinking of poly-(dimethylsiloxane), (2) 425  
 Gas chromatography, use for silicone rubber analysis (review), (3) 437  
 Gas emissions, from passenger tires, (1) 146  
 Gasket, thermoplastic elastomers in, (4) 902  
 Gas-liquid chromatography, accelerator efficiency in model compounds, (5) 1030  
 Gasoline, sour, NBR, resistance to, (2) 331, (4) 883  
 Gel content, of NR, (4) 693  
 Gel permeation chromatography (GPC), NR molecular weight distribution, (4) 693  
 Glass, adhesion to rubber, (1) 23  
 Glass transition temperature ( $T_g$ ), cold crystallization effect, (1) 207  
 rubber adhesion effect, (1) 23  
 Gough-Tangorra equation, elastic constants for rubber-cord composites, (4) 710  
 Green strength, improvement in SBR, (2) 426  
 of radial tire compounds, (4) 897  
 Guayule rubber, chemistry and structure of, (4) 693  
 compounding variations with, (2) 361  
 Guide for Authors, (3) G63  
 Gutta-percha, chemistry and structure of NR from, (4) 693
- Halogen, flame suppressing mechanism of, (2) 430  
 Halogenation, of IR (review), (3) 526  
 Hardness, measurement with spherical indentors, (2) 255  
 Heat build-up, measurement of in tires, (2) 232  
 Heat engine, rubber, analysis of, (1) 159  
 Heat resistance, of bromobutyl rubber, (2) 319  
 of CR in dynamic applications, (4) 781  
 of EPDM cable insulation, (2) 430  
 of NBR, (2) 331  
 of polynorbornene, (4) 903  
 of quinoid vulcanized SBR, (2) 353  
 of silicone elastomers (review), (3) 437  
 Heterogeneity, chemical, of random SBR, (1) 20  
 Hose, fiber orientation in, (4) 838  
 garden, cellulose fiber in (4) 764  
 NBR use for fuel, (4) 883  
 silicone rubber applications in (review), (3) 437  
 Hot melt adhesives, elastomers in, (4) 901  
 HRH bonding systems, effect on dynamic wire adhesion, (4) 805  
 rubber-brass adhesion effect (review), (3) 605  
 Humidity, effect on rolling resistance, (1) 23  
 Hydrogenation, of IR (review), (3) 526  
 Hydrohalogenation, of IR (review), (3) 526  
 Hydroperoxide, in gasoline, NBR resistance to, (2) 331  
 Hydrosilation, silicone rubber cure (review), (3) 437

- Hysteresis, test methods for, in tires, (2) 232
- Image analysis, carbon black structure determination, (2) 377
- Inflation pressure, loss from tubeless tires, (5) 905
- Innerliner, inflation pressure loss through, (5) 905
- Infrared spectroscopy, ATR techniques for NR ozonization, (4) 823
- Infrared vulcanization, of power cable insulation, (2) 433
- Inhibitor, prevulcanization, high temperature vulcanization effect, (4) 725
- Injection molding, polyurethane automotive fascia by RIM, (4) 864
- Innerliner, cellulose fiber in, (4) 764
- Insulation, cable, nonlead stabilizers for, (2) 434
- cable, continuous vulcanization of, (2) 433
- cable, thermoplastic elastomer for, (2) 433
- electrical, EPDM telephone drop wire, (2) 400
- electrical, EPR for, (2) 410
- electrical, nuclear power plant requirements, (2) 432
- electrical salt bath curing of, (2) 432
- EPDM, peroxide curatives for, (2) 431
- wire, flame retardant EPDM, (3) 430
- wire, historical review of elastomers in, (2) 429
- Interlaminar shear, of cord-rubber composites, (4) 792
- Internal mixer, cellulose fiber dispersion in, (4) 764
- effect on functionalized NBR properties, (1) 84
- visualization of flow in, (1) 134
- Iodine, flame suppressing mechanism of, (2) 430
- Isoprene, copolymers with styrene, (2) 278
- properties of (review), (3) 526
- Laminates, rubber-cord, elastic constants for, (4) 710
- rubber-cord, fracture mechanics of, (1) 96
- rubber-cord, interlaminar shear strain, (4) 792
- Latex, NR, perspective and strategies, (2) 426
- Litharge, dispersions in fluoroelastomers, (4) 899
- Lithium, isoprene polymerization initiator (review), (3) 526
- Living polymers, carbon black grafts to, (1) 43
- Loss tangent, of copolymer pressure-sensitive adhesive, (2) 278
- Low temperature properties, of NR, (4) 773
- Magnesium oxide, curative for heat resistant bromobutyl rubber, (2) 319
- Mechanical analysis, of rubber heat engine, (1) 159
- Mechanical rubber goods (MRG), future research directions, (2) 428
- Mechanical properties, of carbon black-polyisoprene graft polymers, (1) 43
- of silicone rubber (review), (3) 437
- Melting point, effect on elastomer cold crystallization rate, (1) 207
- Membranes, silicone rubber applications (review), (3) 437
- Methyl acrylate, copolymer with ethylene, (2) 426
- 2-Methyl-2-pentene, model compound for NR vulcanization, (2) 213; (5) 1030, (5) 1044, (5) 1050
- Microstructure, of polyisoprene (review), (3) 526
- Milkweed, chemistry and structure of NR from, (4) 693
- Milling, band formation analysis during, (2) 387
- effect on functionalized NBR properties, (1) 84
- Mixing, of rubber-fiber composites, (4) 764
- visualization of, in internal mixers, (1) 134
- Model, elastomer, local constraint effect on junctions, (1) 110
- Model compound vulcanization, curative effects, (2) 213, (5) 1030, (5) 1044, (5) 1050
- Modulus, dynamic, entanglement plateau for block polymers, (2) 278
- measurement with spherical indentors, (2) 255
- of NR, (5) 996
- testing for carbon black specifications, (4) 895
- Mold making, silicone rubber applications (review), (3) 437
- Molecular weight between crosslinks ( $M_c$ ), of EPDM-divinylbenzene compounds, (1) 74
- Molecular weight distribution, of NR, (4) 693
- Mooney equation, application to uniaxial compression and tension, (1) 127
- Mooney rheometer, edge effect correction, (5) 962
- Mooney viscosity, viscosity curves from, (1) 9
- Morphology, of peroxide-cured EPDM-divinylbenzene, (1) 74
- of rubber abrasion patterns, (5) 1008
- Natural rubber (NR), blends with SBR/BR, low temperature properties, (4) 735
- carbon black modulus specification in, (4) 895
- chain scission at low temperatures, (4) 773
- chemistry and structure of, (4) 693
- creep resistance of, (1) 50
- dithiodimorpholine accelerators for, (5) 985
- electrical cable specifications for, (2) 431
- filler and temperature effect on EV cure, (2) 263
- high temperature vulcanization of, (4) 725
- ozonization of, (4) 823

- petroleum waxes in, (5) 973
- property comparison with guayule, (2) 361
- relation of modulus to model compound sulfidic product yield, (5) 1044
- research perspectives and strategies, (2) 426
- Neoprene, see polychloroprene
- Networks, rubber, structure calculation for multifunctional junctions, (2) 304
- Nitrile rubber (NBR), antioxidant-bound, (2) 426
  - automatic transmission seals, (4) 900
  - automotive fuel hose, (4) 883
  - cable jacket insulation, (2) 434
  - functionalized, for silica reinforcement, (1) 84
  - gasoline resistance of, (2) 331
  - low temperature properties, (4) 735
  - oil seals, (4) 901
  - processing agent for, (4) 902
- Nitrones, bound antioxidants from, (5) 949
- Nuclear magnetic resonance (NMR), of EPR, (1) 1
- Nuclear power plant, cable insulation requirements, (2) 432
- Oil resistance, of acrylic elastomers, (1) 173
- Oil seals, design variants for, (4) 901
- Optical applications, of silicone rubber, (review), (3) 437
- Oscillating disk rheometer (ODR), carbon black dispersion estimation, (5) 1019
- Organocobalt compounds, dynamic wire adhesion effect, (4) 805
- Organs, artificial, silicone rubber for (review), (3) 437
- Oxidation, of IR (review), (3) 526
- Ozone resistance, of NR containing waxes, (5) 973
  - petroleum waxes for improved, (4) 895
- Ozonization, surface study of NR, (4) 823
- Ozonolysis, of IR (review), (3) 526
- Particle emissions, from passenger tires, (1) 146
- Particle size, carbon black, dynamic property effect, (5) 996
- Peel adhesion, mechanism of, (1) 23
- Peel mechanics, of adhesives, (5) 1057
- 2-Pentadecylbenzoquinone dioxime, SBR vulcanization, (2) 353
- Peroxide, effect on chlorinated polyethylene tensile properties, (2) 434
  - EPDM curative for wire and cable insulation, (2) 431
  - sulfur effect on EPDM cure, (1) 74
- Petroleum wax, bloom of, (5) 973
  - rubber ozone protection by, (4) 895
- N-phenyl nitron, bound antioxidants in non-sulfur vulcanizates, (5) 949
- Photogrammetry, carbon black structure characterization, (2) 377
- Plasticizers, effect on chlorinated polyethylene tensile properties, (2) 434
  - effect on CR high temperature dynamic properties, (4) 781
  - effect on PVC plastisol rheology (review), (3) 676
  - effect on SBR extrusion, (2) 294
  - in bound antioxidant NBR fuel hose, (4) 883
  - low temperature properties, effect on, (4) 735
- Plastics, technology transfer to rubber, (2) 429
- Plastisols, PVC, rheology of (review), (3) 676
- Pollution, air, tire contribution to, (1) 146
- Polyacrylates, automatic transmission seals, (4) 900
  - elastomer, properties of, (1) 173
  - future research trends, (2) 426
  - low temperature properties of, (4) 735
  - oil seals, (4) 901
  - processing agent for, (4) 902
- Polybutadiene (BR), carbon black dispersion in, (5)
  - cold crystallization rate of, (1) 207
  - extrusion shrinkage in SBR blends, (1) 187
  - improved chain linearity in *cis*-, (2) 426
  - polyurethanes from, (5) 920
  - SBR blends, low temperature properties, (4) 735
- Polychloroprene (CR), cable insulation in nuclear power plants, (2) 432
  - cable jackets, (2) 434
  - cold crystallization, rate of, (1) 207
  - creep resistance of, (1) 50
  - high temperature dynamic properties of, (4) 781
  - latex carpet underlayment, (4) 871
  - low temperature properties, (4) 735
- Poly(dimethylsiloxane), see also silicone rubber crosslink distribution effect on properties, (2) 425
  - elasticity of, (1) 127
- Polyepichlorohydrin rubber, future developments, (2) 426
- Polyesters, fiber, use in rubber heat engines, (1) 159
  - films, peel mechanics of, (5) 1057
  - stabilizers for chlorinated polyethylene, (2) 434
- Polyethylene, chlorinated, stabilizer effect on properties, (2) 434
  - chlorosulfonated, cable insulation requirements in nuclear power plants, (2) 432
  - chlorosulfonated, salt bath curing of, (2) 432
  - crosslinked, use in cable insulation, (2) 410
  - use in EPDM cable insulation, (2) 430
- Poly(ethylene terephthalate), peel mechanics for, (5) 1057
- Polyisoprene (IR), bound antioxidants for, (5)
  - carbon black graft, mechanical properties, (1) 43
  - cold crystallization of, (1) 207

- comparison with guayule, (2) 361  
reactions of (review), (3) 526  
structure of (review), (3) 526
- Poly(norbornene (PNR), heat resistance of, (4) 903  
fluid resistance of, (2) 435
- Polyol, polyurea-containing, RIM applications, (4) 864
- Polypropylene, EPDM blend, (2) 429  
impact-resistant, (2) 429
- Polystyrene, high impact, (2) 429
- Poly(thiodiethanol), preparation of, (4) 900
- Polyurea, dispersions for RIM applications, (4) 864
- Polyurethane, block polymers, (2) 429  
elastomer, creep resistance of, (1) 50  
elastomer, from BR, (5) 920  
foam, future research in non-tire uses, (2) 428  
RIM of automotive fascia, (4) 864
- Poly(vinyl chloride) (PVC), cable jacket, usage, (2) 434  
electrical cable, specifications for, (2) 431  
plastisols, rheology of (review), (3) 676
- Power cable, EPR in, (2) 410
- Pressure, loss from tubeless tires, (5) 905
- Pressure sensitive adhesives, elastomers in, (4) 901
- Prevulcanization inhibitor, high temperature vulcanization effect, (4) 725
- Printing, silicone rubber uses in (review), (3) 437
- Process oil, effect on carbon black reinforcement, (4) 748
- Processability, carbon black effect on, (1) 187, (1) 199
- Processing aid, cable insulation uses, (2) 434  
use in elastomers, (4) 902
- Propylene, copolymer with ethylene, NBR analysis of, (1) 1
- Protheses, silicone rubber use in (review), (3) 437
- Quinoid, SBR vulcanization with, (2) 353
- Reaction injection molding (RIM), of polyurea dispersions, (4) 864
- Reinforcement, mechanism, for carbon black-containing elastomers, (1) 43  
of silicone elastomers (review), (3) 437
- Relaxation, mechanism, during extrusion shrinkage, (1) 199  
molecular, effect on extrusion shrinkage, (1) 187
- Reproduction control, silicone rubber for (review), (3) 437
- Resilience, of IR vulcanizates (review), (3) 526
- Rheograph, carbon black dispersion estimated from, (5) 1019
- Rheology, of fiber suspensions, (4) 838  
of PVC plastisols (review), (3) 676
- Rheometer, capillary, carbon black characterization, (2) 429  
capillary, void volume measurements, (4) 896  
Mooney, edge effect correction, (5) 962  
Mooney, viscosity curves from, (1) 9  
Rolling index, test method for, (4) 896  
Rolling resistance, carbon black effect on, (4) 896  
crosslinked SBR effect on, (4) 897  
reduction of, in tires, (2) 428
- Rotor effect, on viscosity curves obtained with Mooney Rheometer, (1) 9
- Rubber-cord laminates, fracture mechanics of, (1) 96
- Rubber Division, ACS, bylaws, (1) G10  
Best Paper Awards, (2) G36, (5) G104  
Charles Goodyear Medalist, (3) G73  
Guide for Authors, (3) G63  
History of Best Paper Awards, (2) G37  
Library and information service, (1) G8, (2) G38, (3) G60, (4) G95  
Officers and committees (1) G1, (2) G33, (3) G57, (4) G87, (5) G101  
Policy on technical papers (1) G23, (2) G48, (3) G62, (4) G97, (5) G107  
Program for Fall meeting 1979, (4) G90  
Program for Spring meeting 1979, (1) G5  
Statistics on 1978 Rubber Chemistry and Technology Papers, (4) G94
- Salt bath, continuous vulcanization of wire and cable insulation, (2) 432
- Scanning electron microscopy, ozone attack of NR, (4) 823
- Seals, automatic transmission, (4) 900  
rotary shaft, (4) 901  
silicone rubber uses (review), (3) 437
- Sequence distribution, of ethylene-propylene copolymers, (1) 1
- Shrinkage, extrusion, carbon black effect, (1) 187  
extrusion, kinetics of, (1) 199
- SI units, use and conversion factors, (1) G24, (2) G49
- Silicone rubber, creep resistance of, (1) 50  
developments (review), (3) 437  
effect of crosslink distribution on properties, (2) 425  
electrical cable specifications for, (2) 431  
processing aid, for, (4) 902  
uniaxial compression and tension, (1) 127
- Solution polymerization, of isoprene (review), (3) 526
- Solvent resistance, of polynorbornene, (2) 435
- Sour gasoline, NBR resistance to, (4) 883
- Springs, rubber, carbon black selection for, (5) 996
- Stabilizer, effect on chlorinated polyethylene tensile properties, (2) 434
- Steel, brass-coated, adhesion to rubber (review), (3) 605  
fracture mechanics of rubber composites, (1) 96
- Squalane, model compound for EPDM, (1) 74

- Storage modulus, of pressure-sensitive adhesives, (2) 278
- Strain, effect on junction displacement of polymer chains, (1) 110
- Stress, shear calculation from Mooney rheometer torque, (1) 9
- Structure, carbon black, characterization of, (2) 377
- carbon black, determination from extrusion shrinkage, (1) 187
- carbon black, effect on dynamic properties, (5) 996
- carbon black, effect on tire tread reinforcement, (4) 748
- Styrene-butadiene rubber (SBR), BR blends, low temperature properties, (4) 735
- carbon black characterization in, (2) 429
- carbon black dispersion in, (5) 1019
- carbon black modulus specification in, (4) 895
- carpet underlayments, (4) 871
- chemical heterogeneity of, (1) 20
- creep resistance of, (1) 50
- electrical cable specifications for, (2) 431
- emissions from passenger tires, (1) 146
- entanglement plateau in dynamic modulus of, (2) 278
- extrusion shrinkage of, (1) 187
- green strength of, (2) 426, (4) 897
- kinetics of extrusion shrinkage, (1) 199
- ultrasonic measurements during extrusion, (2) 294
- vulcanization with 2-pentadecylbenzoquinone dioxime, (2) 353
- Styrene copolymers, with isoprene, entanglement plateau in dynamic modulus of, (2) 278
- Sulfur, EPDM peroxide cure effect of, (1) 74
- level effect in dynamic wire adhesion, (4) 805
- model compound vulcanization with, (2) 213
- Sulfidization, brass-rubber adhesion effect (review), (3) 605
- Surface area, carbon black, reinforcement effect, (4) 748
- Tackifiers, effect on entanglement plateau of block polymer dynamic modulus, (2) 278
- Tear resistance, of IR (review), (3) 526
- Telephone drop wire, EPDM in, (2) 400
- Temperature, reference, optimization for curing cycles, (2) 286
- vulcanization, effect on EV-cured NR, (2) 263
- Tensile creep, of elastomers, (1) 50
- Tensile strength, of IR (review), (3) 526
- test methods for, (2) 232
- Tension, uniaxial, effect on poly(dimethylsiloxane), (1) 127
- Thermal black, effect on NBR aging in sour gasoline, (2) 331
- Thermogravimetric analysis (TGA), of litharge-elastomer dispersions, (4) 899
- of rubber heat engine, (1) 159
- Thermomechanical analysis, low temperature properties, (4) 735
- Thermoplastic elastomers, cable insulation, (2) 433
- cost-performance analysis, (2) 435
- from NR, (2) 426
- gasket uses, (4) 902
- Thiodiethanol, polymerization of, (4) 900
- Tire compounds, green strength of, (4) 897
- Tire cord, acrylic resin adhesives for, (4) 898
- elastic constant for rubber laminates, (4) 710
- interlaminar shear deformations in rubber composites, (4) 792
- steel, adhesion to rubber (review), (3) 605
- trends in tire technology, (2) 428
- Tire emissions, gas and particulate, (1) 146
- Tires, dynamic wire adhesion test for, (4) 805
- inflation pressure loss in, (5) 905
- technology of, current trends, (2) 428
- Tire tread, automatic extrusion of, (4) 903
- carbon black reinforcement of, (4) 748
- dithiodimorpholine accelerators for, (5) 985
- Torque analysis, of rubber heat engine, (1) 159
- Toxicology, of isoprene (review), (3) 526
- Transmission seals, development of, (4) 900
- Tread, tire, automatic extrusion of, (4) 903
- Treadwear, carbon black effect on, (4) 748
- Triazine, NR accelerators from, (5) 1050
- Trimellitic acid, triesters, chlorinated polyethylene stabilizers, (2) 434
- Tubeless tires, inflation pressure loss in, (5) 905
- Ultrasonics, use in rubber extrusion, (2) 294
- Uniformity, mix, visualization of in internal mixers, (1) 134
- V-belt, cellulose fibers in, (4) 764
- Vinyl acetate, copolymer with ethylene, electrical insulation specifications for, (2) 431
- Viscoelasticity, dynamic, of liquid polyurethane, (5) 920
- test methods for, (2) 232
- Viscosity, complex, calculation using Mooney rheometer, (1) 9
- steady state, calculation of, (1) 9
- Void volume, carbon black identification using, (4) 896
- Vulcanization, continuous, of wire and cable insulation, (2) 432
- free radical, of silicone rubber (review), (3) 437
- high temperature, (4) 725
- infrared, of power cable insulation, (2) 433
- model compound, curative effect on, (2) 213, (5) 1030, (5) 1044, (5) 1050
- radiation-induced, of silicone elastomers (review), (3) 437
- room temperature, of silicone elastomers (review), (3) 437
- test methods for properties during, (2) 232

- Water resistance, of EPR power cables, (2) 410
- Wax, petroleum, bloom of, (5) 973
- ozone protection of rubber by, (4) 895
- Whiting, NR property effect of, (2) 263
- Wire adhesion, dynamic test for, (4) 805
- Wire insulation, flame retardant EPDM, (2) 430
- peroxide curatives for EPDM, (2) 431
- review of elastomers in, (2) 429
- thermoplastic elastomer for, (2) 433
- X-ray, interlaminar shear deformations in rubber-cord composites, (4) 792
- X-ray diffraction, of liquid polyurethanes, (5) 920
- Young's modulus, of cord-rubber composites, (4) 710
- of peroxide-cured EPDM-divinylbenzene compounds, (1) 74
- of silica-reinforced functionalized NBR, (1) 84
- Zinc, adhesion to rubber (review), (3) 605
- Zinc oxide, curative for heat resistant bromobutyl rubber, (2) 319
- effect on model compound vulcanization, (2) 213

